Date User: Customer Comment Seq. #:

Dart Aerospace Ltd. Tuesday, 1/8/2008 1:20:26 PM Kim Johnston **Process Sheet** : BEARING ASSEMBLY **Drawing Name** : CU-DAR001 Dart Helicopters Services Job Number : 10716 **Estimate Number** : D3121241 Part Number P.O. Number : 1/8/2008 S.O. No. : **Drawing Number** : D3121 REV E This Issue : N/A : NC Project Number Prsht Rev. : E : MACHINED PARTS First Issue : // **Drawing Revision** Type : 34532 Material Previous Run : 1/31/2008 Each Due Date Qty: 60 Um: Written By Checked & Approved By New issue KJ/DS DD verified by:EC 07-11-12 Est Rev:B ECN 1060 **Additional Product** Job Number: Description: D3121-25 **DELRIN ROUND BAR 1.25"** Batch B36 Comment: Qty.: 0.0546 f(s)/Unit Total: 3.2760 f(s) Material: 31.25 Delrin Rod (M-DELRIN-Rt 2500)Identify as D3121-25 18/0//25 HARDINGE CNC LATHE SMALL 2.0 Comment: HARDINGE CNC LATHE SMALL 1-Turn D3121-25 Cap as per Folio FA387 2-Deburn INSPECT PARTS AS THEY COME OFF MACHINE 3.0 QC2 Comment: INSPECT PARTS AS THEY COME OFF MACHINE SECOND CHECK 4.0 QC8 Comment: SECOND CHECK 5.0 D312123 Bearing Comment: Qty.: 1.0000 Each(s)/Unit B34670×12 Total: 60.0000 Each(s) Pick:

> **Qty Part Number** Description Batch Bearing <u>B</u> 1 D3121-23

And 08/01/25

Dart Ae	rospace l	Ltd							
W /O:			WC	ORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE		Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector	
Part No	:	PAR #:	Fault Cate	gory: NC				Date: <u>/</u>	
NCR:		,	WORK ORDI	ER NON-CONFORMANC	E (NCR)			
		Description of NC		Corrective Action Section B		Verific	ation	Approval	Approval
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Secti		Approval Chief Eng	QC Inspector
				s.					

NOTE: Date & initial all entries

Date: Tuesday, 1/8/2008 1:20:26 PM User: Kim Johnston **Process Sheet** Drawing Name: BEARING ASSEMBLY Customer: CU-DAR001 Dart Helicopters Services Job Number: 36669 Part Number: D3121241 Job Number: Description: Seq. #: Machine Or Operation: SMALL & MEDIUM FAB RESOURCE 1 SMALL FAB 1 6.0 Comment: SMALL & MEDIUM FAB RESOURCE 1 1-Press D3121-23 Bearing into D3121-25 Cap as per Dwg D3121 INSPECT WORK TO CURRENT STEP QC5 7.0 Comment: INSPECT WORK TO CURRENT STEP PACKAGING 1 PACKAGING RESOURCE #1 8.0 Comment: PACKAGING RESOURCE #1 Identify and Stock

Location:

QC21

9.0

Job Completion

Comment: FINAL INSPECTION/W/O RELEASE



FINAL INSPECTION/W/O RELEASE



2008/1/28

Dart Aerospace Ltd

W/O:		WORK ORDER CHANGES							
DATE	STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approva QC Inspector		
Part No	:	PAR #: Fault Category:	NCR: Yes	No DQ	A:	_ Date: _			
			QA:	N/C Close	d:	Date: _			

NCR:			WORK ORDE	ER NON-CONFORMAN	CE (NCR)			
		Description of NC		Corrective Action Section B			A	A
DATE	STEP	Section A	Initial Action Description Chief Eng Chief Eng		Sign & Date	Verification Section C	Approval Chief Eng	Approval QC Inspector

NOTE: Date & initial all entries




	DESIGN DRAWN BY		DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
	CHEC	KED	APPROVED	DRAWING NO. REV. E		
		#		D3121 SHEET 1 OF 10		
	DATE			TITLE SCALE		
	07.1	1.07		BRACKET ASSEMBLY 1:2		
-	Α		02.04.15	NEW ISSUE		
	В	"	03.01.16	ADD RIDGES; ADD MAT'L PROP; FIX P/N ADD -141/-143/-144/-145/-146		
	С		04.02.17	ADD CLEARANCE; USE -241 BEARING		
	D		06.05.17	D3121-25 CAP WAS 1.024, NOW 1.000		
	E		07.11.07	ADD TOLERANCE TO 0.032 (DETAIL B)		



- D3121-2	21 BOLT (1)
D3121-2	241	
BEARING	ASSEMBLY	(1)

D3121-041 BRACKET ASSEMBLY


(REPLACES PREMIER P/N B30-23000-33)



D3121-21 BOLT (1)
D3121-241
BEARING ASSEMBLY (1)
(2 PLACES)

D3121-13/-14 BRACKET D3121-043 (SHOWN) / D3121-044 (OPPOSITE)
BRACKET ASSEMBLY

(REPLACES PREMIER P/N B30-23000-37/-38)



D3121-21 BOLT (1) D3121-241 BEARING ASSEMBLY (1) (2 PLACES)

D3121-15/-16 BRACKET

D3121-045 (SHOWN) / D3121-046 (OPPOSITE)
BRACKET ASSEMBLY

(REPLACES PREMIER P/N B30-23000-35/-36)


SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE

WORK OF DER 9

Copyright © 2002 by DART AEROSPACE LTD



DESIGN	DRAWN BY	DART AEROSP HAWKESBURY, ONTARI	
CHECKED	APPROVED	DRAWING NO.	REV. E
4	-	D3121	SHEET 2 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2





Copyright © 2002 by DART AEROSPACE LTD



DESIGN	DRAWN BY	DART AEROSF HAWKESBURY, ONTAF	
CHECKED	APPROVED,	DRAWING NO.	REV. E
4	-#	D3121	SHEET 3 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:1


DETAIL A: SCALE 2:1 VIEW ROTATED





SECTION C-C


DETAIL B: RIDGE DETAIL PARTIAL SECTION **SCALE 1:20**




SHOP COPY RETURN TO ENGINEERING NCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE

WORK ORDER O







D3121-11 BRACKET

1) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B) MIN ULTIMATE TENSILE = 150 ksi

MIN YIELD TENSILE = 100 ksi

2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

ALL DIMENSIONS ARE IN INCHES

4) BREAK ALL SHARP EDGES 0.005 TO 0.015

5) ENGRAVE DART P/N & LOGO AS SHOWN

6) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005

SHOP COPY RETURN TO ENGINEERING

UNCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE

NO. 366

Copyright © 2004 by DART AEROSPACE LTD




DESIGN #	DRAWN BY	DART AEROSP HAWKESBURY, ONTAR	
CHECKED	APPROVED	DRAWING NO.	REV. Ē
4	 	D3121	SHEET 5 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2


0.300

DRILL #21 (Ø0.159) TAP 10-32UNF-3B THRU,

C'BORE Ø0.201x0.100

(2 PLACES)





1.800

0.080

D3121-13 BRACKET (SHOWN) D3121-14 BRACKET (OPPOSITE)

1.280

1) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B)

MIN ULTIMATE TENSILE STRENGTH = 150 ksi MIN YIELD TENSILE STRENGTH = 100 ksi

2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

3) ALL DIMENSIONS ARE IN INCHES

4) BREAK ALL SHARP EDGES 0.005 TO 0.015

5) ENGRAVE DART P/N & LOGO AS SHOWN

6) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005

SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY


SUBJECT TO AMENDMENT
WITHOUT NOTICE

WORK ORDER ON SOLO OF THE NO. 3000

Copyright © 2002 by DART AEROSPACE LTD



DESIGN #	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
CHECKED A	APPROVED	DRAWING NO.	REV. E	
#	9	D3121	SHEET 6 OF 10	
DATE	1 -,,,,,,	TITLE	SCALE	
07.11.07		BRACKET ASSEMBLY	1:2	



D3121-15 BRACKET (SHOWN) D3121-16 BRACKET (OPPOSITE)

1) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B)

MIN ULTIMATE TENSILE = 150 ksi

MIN YIELD TENSILE = 100 ksi

2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

3) ALL DIMENSIONS ARE IN INCHES

4) BREAK ALL SHARP EDGES 0.005 TO 0.015

5) ENGRAVE DART P/N AND LOGO AS SHOWN

6) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005

SHOP COPY RETURN TO ENGINEERING


UNCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE

WORK ORDER 9

Copyright © 2002 by DART AEROSPACE LTD



DESIGN #	DRAWN BY	DART AEROSP HAWKESBURY, ONTARI	
CHECKED	APPROVED	DRAWING NO.	REV. E SHEET 7 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2



D3121-111 BRACKET

- 1) REPLACES PREMIER P/N B32-23001-11
- 2) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B)

MIN ULTIMATE TENSILE = 150 ksi

MIN YIELD TENSILE = 100 ksi


- 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHEWISE NOTED
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) BREAK ALL SHARP EDGES 0.005 TO 0.015
- 6) ENGRAVE DART P/N & LOGO IN AREAS SHOWN
- 7) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005

SHOP COPY RETURN TO **ENGINEERING** UNCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE

Copyright © 2002 by DART AEROSPACE LTD





DESIGN #	DRAWN BY	DART AEROS HAWKESBURY, ON	
CHECKED _	APPROVED	DRAWING NO.	REV. E
4	-#	D3121	SHEET 8 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2




Copyright © 2002 by DART AEROSPACE LTD











D3121-21 BOLT (SCALE 1:1)

OTHERWISE NOTED

4) ALL DIMENSIONS ARE IN INCHES

1) MATERIAL: AISI 303 SS HEX, ANNEALED

3) TOLERANCES ARE PER DART QSI 018 UNLESS

5) BREAK ALL SHARP EDGES 0.005 TO 0.015

 0.230 ± 0.001

TAP 10-32

UNF-3A

- 0.050 TO 0.060

- 0.080

(REF DART SPEC. M303H0.500)

0.315

1.000 0.838

R0.063

±0.002


R0.010

0.865

 ± 0.001


0.375 -

2) FINISH: NONE




D3121-17 WASHER (SCALE 2:1)

- 1) REPLACES PREMIER P/N B32-23001-17
- 2) MATERIAL: AISI 303 SS ROUND BAR, ANNEALED (REF DART SPEC. M303R)
- 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) BREAK ALL SHARP EDGES 0.005 TO 0.015



D3121-19 BEARING (SCALE 1:1)

- 1) POSSIBLE SUPPLIER: KING BEARING P/N 6000-2ZJ/EM FAFNIR P/N 9100KDD
- 2) ALL DIMENSIONS ARE IN INCHES




D3121-23 BEARING (SCALE 1:1)

1) POSSIBLE SUPPLIER: SKF P/N 61900-2Z OR KML P/N 6900-ZZ

2) ALL DIMENSIONS ARE IN INCHES

1) MATERIAL DELRIN ROD Ø

- 1) MATERIAL: DELRIN ROD, Ø1.25 (REF DART SPEC. M-DELRIN-R1.250)
- 2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 3) ALL DIMENSIONS ARE IN INCHES



D3121-241 BEARING ASSEBLY (SCALE 1:1)

Copyright © 2002 by DART AEROSPACE LTD